

## Column Speakers

### Indoor (GRAY)



CS-710/720/730/740  
(10W/20W/30W/40W)

spec \ model	Unit	CS-710	CS-720	CS-730	CS-740
Rated Output	W	10	20	30	40
Impedance	Ω	1k/2k	500/1k	330/660	250/500
Frequency Response	Hz	200 ~ 14k	200 ~ 14k	200 ~ 14k	200 ~ 14k
S.P.L.   1m/1W	dB	88	90	91	93
Enclosure Material		Aluminum			
Weight	kg	1.6	2.9	3.8	4.6
Dimensions(WxHxD)	mm	138x253x105	138x326x105	138x453x105	138x580x105

### Outdoor



CS-810/820/830/840  
(10W/20W/30W/40W)

spec \ model	Unit	CS-810	CS-820	CS-830	CS-840
Rated Output	W	10	20	30	40
Impedance(100Volt)	Ω	COM 1k/10W 2k/5W	COM 500/20W 1k/10W	COM 330/30W 660/15W	COM 250/40W 500/20W
Frequency Response	Hz	200 ~ 22k	200 ~ 22k	200 ~ 22k	200 ~ 22k
S.P.L.   1m/1W	dB	92	95	96	99
Enclosure Material		Aluminum			
Weight	kg	2.9	3.6	4.7	5.4
Dimensions(WxHxD)	mm	149x310x124	149x420x124	149x530x124	149x640x124

### Indoor



CS-910/920/930/940  
(10W/20W/30W/40W)

spec \ model	Unit	CS-910	CS-920	CS-930	CS-940
Rated Output	W	10	20	30	40
Impedance	Ω	1k/2k	500/1k	330/660	250/500
Frequency Response	Hz	250 ~ 14k	250 ~ 14k	250 ~ 14k	250 ~ 14k
S.P.L.   1m/1W	dB	88	90	91	93
Enclosure Material		Aluminum			
Weight	kg	1.4	2.5	3.6	4.7
Dimensions(WxHxD)	mm	104x300x86	104x478x86	104x656x86	104x834x86

## Wall Speakers



SWS-03A(BR, IV)  
(3W)



SWS-10A(BR, IV)  
(10W)

- Inter-M's stylish new SWS series offer a break from the conventional 'Box' speaker. With either 3W or 10W 100V line versions available, these are the ideal choice for an office environment. The SWS-03 and SWS-10 are available in an off-white or brown finish.

spec \ model	Unit	SWS-03(A)	SWS-10(A)
Rated Output	W	3 / 2 / 1 100V	10 / 5 / 3 100V
Frequency Response	Hz	150 ~ 12k	150 ~ 12k
S.P.L.   1m/1W	dB	89	90
Colour		Off White or Brown	Off White or Brown
Material		Injection Moulded	Injection Moulded
Weight	kg	1.1	1.34
Dimensions(WxHxD)	mm	140 x 274 x 120	140 x 274 x 120