

Paging Horn Speakers



spec \ model	Unit	HS-S20	HS-20	HS-30	HS-50	HS-30RT	HS-40RT
Rated Output	W	20	20	30	50	30	40
Impedance	Ω	500, 1k	500, 1k	330, 660	200, 400	330, 660	250, 500
Frequency Response	Hz	380 ~ 6500					
S.P.L 1m/1W	dB	106	106	107	109	107	109
Weight	kg	1.5	2.45	2.85	3.1	2.95	2.95
Dimensions	mm	169(Ø) x 230(D)	250(Ø) x 280(D)	280(Ø) x 350(D)	320(Ø) x 350(D)	320(W) x 210(H) x 365(D)	

Clear Horn Speaker



CH-530(30W) : 4" Full Range
CH-532(30W) : 4" Coaxial Cone

- Indoor or outdoor use
- Coaxial type 2 way system
- Wide frequency range & vocal clarity
- Excellent for public address systems
- Easy installation
- Dispersion control

spec \ model	Unit	CH-522	CH-532
Rated Input	W	20	30
Impedance	Ω	500 ~ 1k	165 ~ 330
Frequency Response	Hz	110 ~ 20k	100 ~ 20k
S.P.L(1m/1W)	dB	95	95
Weight	kg	3.5	
Dimensions(WxHxD)	mm	294 x 209 x 326	

Attenuator Unit



ATT-01
(1W)

ATT-03
(3W)

ATT-30
(30W)

- Switch-plate-mounted attenuator unit
- Attractive modern design
- Simple installation
- Screwless terminal block makes wiring very easy

spec \ model	Unit	ATT-01	ATT-03	ATT-30
Rated Input	W	1	3	30
Application	W	1	2 ~ 3	7 ~ 30
Input Impedance (Reference Voltage 100V)	Ω	10k	5k ~ 3.3k	1.4k ~ 330
Volume Control	dB	4 step SW (-off, -10, -4, 0dB)	4 step SW (-off, -10, -4, 0dB)	4 step SW (-off, -12, -6, 0dB)
Method		Resistor	Resistor	Transformer
Material	Plate	SECC 1.0t		
	Front Cover	A.B.S		
Weight	g	109	112	196
Dimensions(WxHxD)	mm	68 x 120 x 38		