

Microphones

Dynamic Type



MD-600 MD-700 MD-750 MD-850 MD-950

spec \ model	Unit	MD-600	MD-700	MD-750	MD-850	MD-950
Type		Dynamic				
Polar Pattern		Cardioid	Unidirectional	Cardioid	Super Cardioid	Super Cardioid
Frequency Response	Hz	80~13,500	-	80~14,000	70~15,000	70~16,000
Sensitivity	dB	-54±3	-54±3	-54	-52	-52 ±3
Impedance	Ω	600±30%	600±30%	580	600	600
Weight	g	245	265	300	320	320
Dimensions	mm	52(Ø)x168(D)	54(Ø)x176(D)	54(Ø)x178(D)	55(Ø)x180(D)	55(Ø)x180(D)

Condenser Type



MC-1000

spec \ model	Unit	MC-1000
Type		Electric Condenser
Polar Pattern		Cardioid
Frequency Response	Hz	70 ~ 17,000
Sensitivity	dB	-50
Impedance	Ω	600
Output Connector		XLR M-TYPE
Battery	V	1.5V AA/UM3
Weight	kg	270 (with Battery)
Dimensions	mm	26(Ø) x 186

RM-01

Remote Microphone Station



- Unidirectional dynamic microphone
- Remote chime switch
- Mic on/off switch
- 2 Push buttons for easy operation
- Weight : 1.4kg / 3lb
- Dimensions : 90(W)X45(H)X133(D)mm / 3.5(W)X1.8(H)X5.2(D)in

RM-916

Remote Paging Mic Station



- Output : Program output (balanced)
- Input : AUX (unbalanced)
- 16 Speaker control terminals & switches
- All call switch
- 4 Tone chime for announcement
- Mute switch
- Power Source : DC 24V
- Weight : 1.2kg / 2.6lb (without microphone)
- Dimensions : 245(W)X60(H)X205(D)mm / 9.6(W)X2.3(H)X8(D)in