

PA-920/935 Mixer/Amplifier



CE

- Output Power : PA-920 : 20W(RMS) < 1% THD
PA-935 : 35W(RMS) < 1% THD *
- Inputs : Mic 1, Mic 2 (AUX 1), Mic 3 (AUX 2), telephone input
- 2 Band Equalizer : ± 10 dB
- Priority Muting : Mic1, telephone, adjustable independently
- Power Source : 100-120VAC or 220-240VAC; 50/60Hz
(supplied AC mains transformer depends on country requirements)
- Power Consumption : PA-920 : 50W, PA-935 : 80W
- Weight : PA-920 : 3.5kg / 7.7lb, PA-935 : 4.4kg / 9.7lb
- Dimensions : 290(W)X76(H)X196(D)mm / 11.4(W)X3(H)X7.7(D)in

PA-1000B/1000BR Mixer/Amplifier/Receiver



CE

- Output Power : 30W(RMS) < 1% THD
- Inputs : Mic 1, Mic 2, AUX, telephone input
- Input Connectors : Mic : Balanced XLR and 1/4"
Telephone input : Screw terminal
- 2 Band Equalizer : ± 10 dB
- Priority Muting : Mic 1, telephone, adjustable independently
- Remote controllable 4 tone chime for pre-announcement signal
- Line in/out for additional mixer or amp link
- PA-1000BR Only : AM/FM digital tuner with 30 programmable presets
memory with music on hold
- Power Source : 100-120VAC or 220-240VAC; 50/60Hz
(supplied AC mains transformer depends on country requirements)
- Power Consumption : 80W
- Weight : PA-1000B : 4.6kg / 10lb, PA-1000BR : 4.8kg / 11.5lb
- Dimensions : 300(W)X88(H)X260(D)mm / 11.8(W)X3.5(H)X10.2(D)in

A-60/120 Mixer/Amplifier



CE

- Output Power : A-60 : 60W(RMS) < 1% THD
A-120 : 120W(RMS) < 1% THD
- Inputs : Mic1-3(1/4" balanced), AUX1-2
- 2 Band Equalizer : ± 12 dB
- Priority Muting : Mic 1
- Power Source : 100-120VAC or 220-240VAC; 50/60Hz
(supplied AC mains transformer depends on country requirements)
- Power Consumption : A-60 : 75W, A-120 : 105W
- Weight : A-60 : 8.9kg / 19.6lb, A-120 : 10.3kg / 22.7lb
- Dimensions : 420(W)X88(H)X320(D)mm / 16.5(W)X3.5(H)X12.6(D)in

PA-2000/4000 Mixer/Amplifier



CE

- Output Power : PA-2000 : 60W(RMS) < 1% THD
PA-4000 : 120W(RMS) < 1% THD
- Inputs : 6 Balanced with adjustable sensitivity
Options : XLR, 1/4", RCA, screw terminal
Telephone Input : Screw terminal
- Priority Muting : Ch1, 2, chime & siren, telephone input adjustable
- 5 Band Equalizer : 100, 330Hz, 1, 3.3, 10kHz ± 12 dB
- Remote controllable 4 tone chime for announcement and siren
- Line in/out for additional mixer or amp link
- 5 Individual speaker zone selector and all call
- Power Source : 100-120VAC or 220-240VAC; 50/60Hz
(supplied AC mains transformer depends on country requirements)
- Power Consumption : PA-2000 : 150W, PA-4000 : 300W
- Weight : PA-2000 : 10kg / 22lb, PA-4000 : 12kg / 26.4lb
- Dimensions :
PA-2000 : 420(W)X100(H)X320(D)mm / 16.5(W)X3.9(H)X12.6(D)in
PA-4000 : 420(W)X133(H)X320(D)mm / 16.5(W)X5.2(H)X12.6(D)in