

## Mic Amplifier



PS-30(30W)

- Integrated 30 watt powered speaker
- 2 Way system with HF driver and LF woofer
- Compact, strong, structural-foam enclosure
- Covered in rugged carpet material to resist scuffs and bumps in transit
- Corner protectors and metal grilles are standard for added protection
- 2 Low impedance microphone inputs & 1 AUX input

spec	model	Unit	PS-30
Rated Output		W	30
Input Sensitivity / Impedance	MIC 1,2	Ω	-50dB/600, BAL
	AUX	Ω	-10dB/10k, UNBAL
Frequency Response	Mic Input	Hz	250 ~ 12k
	AUX	Hz	80 ~ 18k
S.P.L	1W/1m	dB	90
Power Source		V	AC 120V/230V/240V, 50/60Hz, DC 12V
Power Consumption		W	120V : 18W, 230V : 23W, 240V : 19W
Weight		kg	4.6
Dimensions(WxHxD)		mm	345 x 205 x 173

## Fashion Speakers



FS-52

- 50W
- 1" Dome Tweeter
- 5" 1/4 Cone Woofer
- 3.74"x3.74" Horn



FS-30/60/100

- 30W/60W/100W
- 5" Full Rangex2



FSB-2

- Designed for high quality, professional sound reproduction
- A switch permits connection to either low impedance (8ohm) or high Impedance (70/100V line) loudspeaker systems(FS-30/60/100)
- Full range 5 1/4"x2"(FS-30/60/100)
- 2Way 1"+5 1/4"(FS-52)
- FS-52 available only in 8ohm version
- Colour coded connection terminals, red=positive(+) and black=negative(-)
- Connection terminals are push type to allow easy cable connection

spec	model	Unit	FS-30	FS-60	FS-100	FS-52
Rated Output		W	30	60	100	50
Impedance		Ω	8/333	8/167	8/100	8
Frequency Response		Hz	180 ~ 13k			
Dimensions(WxHxD)		mm	175 x 300 x 158.5			
Bracket (Option)			FSB-2			



MS-50BT  
(20W)

- 20W @ 4Ω or 20W @ / 100V
- 2" 1/4 Cone Tweeter
- 5" Cone Woofer



MS-50WT  
(20W)

- 20W @ 4Ω or 20W @ / 100V
- 2" 1/4 Cone Tweeter
- 5" Cone Woofer



FSB-1

- Built-in matching transformer for public address system
- Rated input: 20Watt/4ohm or 100V speaker line
- Compatible to FSB-1 bracket
- Attractive styling

spec	model	Unit	MS-50BT	MS-50WT
Rated Output		W	20Watt/4ohm or 20Watts/100V speaker line	
Frequency Response		Hz	120 ~ 20k	
S.P.L	1m/1W	dB	90	
Colour			Black	White
Weight		kg	3.2	
Dimensions(WxHxD)		mm	150 x 240 x 150	
Bracket (Option)			FSB-1	