

Speed Dome Camera



Main Feature :

- 1.4.5"ultra speed ball quick scanning
- 2.480TVL 0.1LUX digital Color Built-In decoder
- 3.Horizontal: 360°0~12°/S
tilting: 90°0~32°/S
- 4.Auto Plus, Anti-flashing Function
- 5.6 Scanning track,32 presetting Position
- 6.Lens: Fixed lens: 2.8 – 16mm
- 7.Installing type: Ceiling, Wall Open
Agreement RS-485

•External dimensions

GS-706HB

1/3"COLOR SONY CCD,
480TVL,0.1LUX ,Fix 6mm lens

OS-27S1

1/3"Color Sony Super Exview CCD,520TVL,0.5LUX,
auto white balance backlight compensation,
with fix 6mm lens

•Specification

MODEL	GS-706HB	OS-27S1
Effective Pixel	NTSC : 537×505	NTSC:811×508
	PAL : 537×597	PAL:795×596
Sync.System	Internal	
Resolution	480TVL	520TVL
Minimum Illumination	0.1LUX	0.5LUX
S/N Ratio	≥48dB	
Gain Control	Auto	
White Balance	Auto (2500°K~9500°K)	
Electronic Shutter	Auto E Shutter:1/60(1/50)~1/100000 Sec	
Back light Compensation	On/off Switchable	
Lens Mount Type	6MM	
Video Output	1.0Vp-p,75Ω	
Power Consumption	4W	
Power Supply	DC12V	
Operation Temp	-10°C~+50°C	
Size	φ185×172mm	
Size of Carton (CM)	69*37*43	
20" container (28CBM)	250CTNS	